EHF Order response 1.0

Message Guideline

Element	Name	Req.	Card.	Description	Rule	Example
OrderResponse	EHF Order response	М		Norwegian implementation of the CEN BII Order respons		
-cbc:UBLVersionID	UBL VersionID	1	1	UBL Version the message is based on	NOGOV-T76-R007	M
-cbc:CustomizationID	Customization identifier	1	1	Identifies the specification of content and rules that apply to the transaction.		M
-cbc:ProfileID	Profile identifier	1	1	Identifies the BII profile or business process context in which the transaction appears.	BII2-T76-R002, EHFPROFILE-T76-R001	M
—ebc:ID	Order response identifier	1	1	A transaction instance must have an identifier. The identifier enables referencing the transaction for various purposes such as from other transactions that are part of the same process.		М
-cbc:IssueDate	Order response issue date	1	1	The date on which the transaction instance was issued.	BII2-T76-R004, NOGOV- T76-R001	M
-cbc:IssueTime	Order response issue time	0	1	The time assigned by the buyer on which the transaction was issued.		О
cbc:OrderResponseCode	Response code	1	1	A code that indicates whether the referenced order as whole is Accepted or Rejected or, alternatively, Accepted with change. If response code is Accept or Reject there may not be any response lines. Valid codes are: 29 (Accepted), 27 (Rejected) and 30 (Accepted with change)	BII2-T76-R033, OP-T76- R001	M
@ listID	Codelist for OrderResponseCode	required		UNCL1225	EUGEN-T76-R003	
—cbc:Note	Response clarification	0	1	Clarifacation of the suppliers decision.		О
_cbc:DocumentCurrencyCode	Document currency	1	1	The default currency for the offer.	OP-T76-R003	M
└─ @ listID	Codelist for currency code	required		ISO4217		
-cac:OrderReference	OrderReference	1	1	Order reference information		
_cbc:ID	Order document reference	1	1	Used to reference the order that is being responded to.	BII2-T76-R032	M
_cac:SellerSupplierParty	Seller	1	1	Information about Seller		
cac:Party	Party	0	1	Party information		
cbc:EndpointID	Seller party endpoint identifier	0	1	Identifies the end point of the routing service, e.g., EAN Location Number, GLN.	NOGOV-T76-R003, NOGOV-T76-R006	R
@ schemeID	Code for issuer	required		Must be according to "PEPPOL policy for identifiers", example NO:ORGNR	EUGEN-T76-R001, NOGOV-T76-R002	

EHF Order response 1.0

Message Guideline

ement	Name	Req.	Card.	Description	Rule	Example
cac:PartyIdentification	Party Identification	0 .	. unbounded	Information about PartyID		
cbc:ID	Seller party identification	1 .	. 1	Identifies a party.	BII2-T76-R022	D
@ schemeID	Code for issuer	required		Must be according to "PEPPOL policy for identifiers", example GLN	EUGEN-T76-R002	
cac:PartyName	Party name	0 .	. 1	Information about Party name		
cbc:Name	Seller party name	1 .	. 1	The name of the party.	BII2-T76-R022	D
cac:Contact	Contact	0.	. 1	Contact information for Seller		
—cbc:Name	Contact person name	0.	. 1	The name of the contact person.		О
cbc:Telephone	Contact telephone number	0 .	. 1	A phone number for the contact person. If the person has a direct number, this is that number.		О
—cbc:Telefax	Contact fax number	0.		A fax number for the contact persons.		0
-cbc:ElectronicMail	Contact email address	0 .	. 1	The e-mail address for the contact person. If the person has a direct e-mail this is that email.		О
-cac:BuyerCustomerParty	Buyer	1 .	. 1	Information about Buyer		
cac:Party	Party	0 .	. 1	Party information		
-cbc:EndpointID	Buyer party endpoint identifier	0.	. 1	Identifies the end point of the routing service.	NOGOV-T76-R003, NOGOV-T76-R005	R
@ schemeID	Code for issuer	required		Must be according to "PEPPOL policy for identifiers", example NO:ORGNR	EUGEN-T76-R001, NOGOV-T76-R002	
cac:PartyIdentification	PartyIdentification	0 .	. unbounded	Information about PartyID		
cbc:ID	Buyer party identification	1 .	. 1	An identification for the buyer party.	BII2-T76-R021	D
@ schemeID	Code for issuer	required		Must be according to "PEPPOL policy for identifiers", example GLN	EUGEN-T76-R002	
cac:PartyName	Party name	0 .	. 1	Information about Party name		
cbc:Name	Buyer party name	1 .	. 1	The name of the party who ordered the items and receives the response.	BII2-T76-R021	D
cac:Contact	Contact	0.	. 1	Contact information		
cbc:ID	Contact ID	0.	. 1	Contact identifier for buyer contact person		O
cac:Delivery	Delivery	0 .	. 1	Delivery information		
-cac:PromisedDeliveryPeriod	Promised Delivery period	1 .	. 1	Information about Promised Delivery period	NOGOV-T76-R004	
—cbc:StartDate	Period start date	0 .	. 1	The date on which the period starts. The start dates counts as part of the period. format YYYY-MM-DD	NOGOV-T76-R001	О

EHF Order response 1.0

Message Guideline

Element	Name	Req.	Card.	Description	Rule	Example
└─cbc:EndDate	Period end date	0 .		The date on which the period ends. The end date counts as part of the period. format YYYY-MM-DD	NOGOV-T76-R001	O
cac:OrderLine	Order line	0 .	. unbounded	Order lines are only sent if Action code on header level is Accepted with change		
cac:LineItem	Line item	1 .	. 1	Line item information		
-cbc:ID	Document line identifier	1 .	. 1	Identifies the response line.	BII2-T76-R003	М
-cbc:Note	Response clarification	0 .	. 1	Clarifacation of the suppliers decision for the line.		О
cbc:LineStatusCode	Response code	1 .	. 1	A code that indicates whether the referenced order line as whole is Accepted or Rejected or, alternatively, Accepted with change. Valid codes are: 29 (Accepted), 27(Rejected), 30(Accepted with change)	OP-T76-R002	M
@ listID	Codelist for LineStatusCode	required		UNCL1225	EUGEN-T76-R004	
—cbc:Quantity	Quantity	0.	. 1	The quantity of items that will be delivered.		О
— @ unitCode	Unit code	required		Must be a valid value in codelist UN/ECE Rec 20	OP-T76-R006	
@ unitCodeListID	Unitcode, codelist	required		UNECERec20		
cac:Delivery	Delivery	0 .	. 1	Delivery information		
-cac:PromisedDeliveryPeriod	Promised Delivery period	1 .	. 1	Information about Promised Delivery period	NOGOV-T76-R004	
-cbc:StartDate	Period start date	0 .	. 1	The date on which the period starts. The start dates counts as part of the period. format YYYY-MM-DD	NOGOV-T76-R001	О
cbc:EndDate	Period end date	0 .	. 1	The date on which the period ends. The end date counts as part of the period. format YYYY-MM-DD	NOGOV-T76-R001	О
cac:Price	Price	0 .	. 1	Price information		
-cbc:PriceAmount	litem price	1 .	. 1	The net price of an item including discounts or surcharges that apply to the price. Although price is an optional element in an offer it recommended as best practice to either state the price or provide reference to an appropriate source from which the price can be identified such as a contract, catalogue or a quote The price amount. The net price of the item including all allowances, charges and taxes but exluding VAT.		O

1.0 EHF Order response

Message Guideline

nent	Name	Req.	Card.	Description	Rule	Example
@ currencyID	Currency code	required		Must be according to ISO4217		
cbc:BaseQuantity	Item price base quantity	0	1	The actual quantity to which the price applies.		О
— @ unitCode	Unit code	required		Must be a valid unit code according to UN/ECE Rec 20		
@ unitCodeListID	Unit code, codelist	required		UNECERec20		
cac:Item	Item	1	1	Item information		
—cbc:Name	Item name	0	1	A short name optionally given to an item, such as a name from a Catalogue, as distinct from a description. A short name for the item.		О
cac:SellersItemIdentification	Sellers Item Identification	0	1	Information about Sellers ItemID		
-cbc:ID	Item sellers identifier	1	1	Associates the item with its identification according to the seller's system. The sellers ID for the item.		О
cac: StandardItemIdentification	Standard Item identification	0	1	Information about Standard ItemID		
cbc:ID	Item standard identifier	1	1	Associates the item with its identification according to a standard system. Standarized ID for the item		О
— @ schemeID	Code for issuer	optional		Example: GTIN		
-cac:SellerSubstitutedLineItem	Substituted Line item	0	1	Information about Substituted Line item		
—cbc:ID	Substituted Line Item ID	1	1	Identifier for Seller Substituted Line Item		М
cac:Item	Item	1	1	Item information		
—cbc:Name	Item name	0	1	A short name optionally given to an item, such as a name from a Catalogue, as distinct from a description. A short name for the item.		О
cac:SellersItemIdentification	Sellers Item identification	0	1	Information about Sellers ItemID		
└─cbc:ID	Item sellers identifier	1	1	Associates the item with its identification according to the seller's system. The sellers ID for the item.		Ο
cac: StandardItemIdentification	Standard Item identification	0	1	Information about Standard ItemID		
cbc:ID	ltem standard identifier	1	1	Associates the item with its identification according to a standard system. Standarized ID for the item		О
@ schemeID	Code for issuer	optional		Example: GTIN		

EHF Order response 1.0

Message Guideline

lement	Name	Req.	Card.	Description	Rule	Example
cbc:ItemClassificationCode	Item commodity classification	1 .	. 1	A classification code for classifying the item by its type or nature.		О
— @ listID	Classification, codelist	optional		Example: UNSPC		
-cac:ClassifiedTaxCategory	Vat category	0 .	. 1	Information about Vat category		
cbc:ID	Item VAT category code	1 .	. 1	The VAT code that indicates what VAT details apply to the item.	OP-T76-R008	О
@ schemeID	Codelist	required		UNCL5305		
-cbc:Percent	Item VAT rate	0 .	. 1	The VAT percentage rate that applies item, unless exemption reasons apply.		О
cac:TaxScheme	Tax scheme	1 .	. 1	Information about Tax scheme (VAT)		
-cbc:ID	Tax Scheme	1 .	. 1	=VAT	NOGOV-T76-R008	
cac:AdditionalItemProperty	Additional Item property	0 .	. unbounded	Information about Additional Item properties for substitution item		
—cbc:Name	Name	1 .	. 1	The name of the information. The name of the item property.		М
—cbc:Value	Value	1 .	. 1	The value of the information. The item property value.		М
cbc:ValueQuantity	Quantity	0.	. 1	Quantity for the property	NOGOV-T76-R009	0
— @ unitCode	Unit code	required		Valid code according to code list UN/ECE Rec20		
@ unitCodeListID	Codelist ID	required		UNECERec20		
-cbc:ValueQualifier	Qualification of qty	0.	. 1	Description of quantity		0
_cac:OrderLineReference	Order Line reference	1 .	. 1	Information about Order Line reference		
└─cbc:LineID	Order line reference	1 .	. 1	Used to reference the initial order line that correspondes to the response. Each order line may only be referenced once. All order lines should be stated.	BII2-T76-R034	M